



Click Wrenches

Interchangeable Standard Preset Click Wrench



Features

- Torque adjustable via setting key
- Tamper proof for production use

Code	Fitting Size	Torque Range	Length	Width	Lf	Weight
	mm	N-m	mm	mm	mm	g
113 41 0006	9 x 12	1-6	125	26	18	160
113 41 0012	9 x 12	2-12	125	26	18	160
113 41 0025	9 x 12	2-25	180	28.6	169	240
113 41 0035	9 x 12	3-35	180	28.6	169	240
113 41 0050	9 x 12	5-50	242	28.6	260	310
113 41 0085	9 x 12	8-85	333	33.5	297	540
113 41 0100	9 x 12	10-100	333	33.5	297	540
113 41 0150	9 x 12	15-150	365	39.5	318	800
113 41 0200	14 x 18	20-200	478	39.5	436	1140
113 41 0340	14 x 18	30-340	538	39.5	501	1250
113 41 0420	14 x 18	40-420	585	39.5	546	1330
Accessories						

113 41 9001 Setting key



Click Wrenches

Dual Way Click Wrench



Features

- Easy torque adjustment (vernier scale), for light production, repair, maintenance and service environment
- Supplied with fixed ratchet

Code	Square Drive	Main Torque Range	Secondary Torque Range	Fine Scale	Length	Width	Lf	Weight
		N-m	lbf-in	N-m	mm	mm	mm	kg
113 43 0005	1/4"	1-5	6.6-46.5	0.05	193	20.2	155	0.2
113 43 0010	1/4"	2-10	13.3-92.9	0.05	193	20.2	155	0.2
113 43 0025	1/4"	5-25	39.8-225.7	0.1	245	27.3	195.2	0.4
113 43 0026	3/8"	5-25	39.8-225.7	0.1	245	27.3	195.2	0.45
113 43 0050	3/8"	10-50	9.2-38.7	0.5	410	36.4	329.5	1.1
113 43 0100	3/8"	20-100	9.2-75.6	0.5	410	36.4	329.5	1.2
113 43 0101	1/2"	20-100	9.2-75.6	0.5	410	36.4	329.5	1.3
113 43 0200	1/2"	40-200	18.4-151.2	1	520	41	435.5	1.6
113 43 0340	1/2"	60-340	36.9-258.1	2	610	41	525	1.7
113 43 0341	3/4"	60-340	36.9-258.1	2	610	41	525	1.76
113 43 0550	3/4"	110-550	83-414.9	2.5	1012	58	918.8	5.4
113 43 0750	3/4"	150-750	92.2-571.6	5	1125	58	1031.8	6
113 43 0751	1"	150-750	92.2-571.6	5	1125	58	1031.8	6
113 43 1000	1"	200-1000	92.2-756	5	1225	67	1127.6	6.5





Click Wrenches

Interchangeable Dual Way Click Wrench

Click Wrenches

Interchangeable Screen Torque Click Wrench

Torque Wrenches

Torque Wrenches



Features

- Easy torque adjustment (vernier scale), for light production, repair, maintenance and service environment
- Supplied with interchangeable end-fitting

Features

- Easy torque adjustment (dial), for light production, repair, maintenance and service environment
- Supplied with interchangeable end-fitting

Code	Fitting Size	Main Torque Range	Secondary Torque Range	Fine Scale	Length	Width	Lf	Weight
	mm	N-m	lbf-in	N-m	mm	mm	mm	kg
113 42 0005	9 x 12	1-5	6.6-46.5	0.05	177	20	138	0.18
113 42 0010	9 x 12	2-10	13.3-92.9	0.05	177	20	138	0.18
113 42 0025	9 x 12	5-25	39.8-225.7	0.1	230	27	177	0.34
113 42 0050	9 x 12	10-50	9.2-38.7	0.5	370	36	297	1.05
113 42 0100	9 x 12	20-100	9.2-75.6	0.5	370	36	297	1.1
113 42 0200	14 x 18	40-200	18.4-151.2	1	487	36	408	1.4
113 42 0340	14 x 18	60-340	36.9-258.1	2	577	36	498	1.5



Code	Fitting Size	Main Torque Range	Fine Scale	Length	Width	Lf	Weight
	mm	N-m	N-m	mm	mm	mm	kg
113 44 0050	9 x 12	10-50	0.5	356	32	298	0.89
113 44 0100	9 x 12	20-100	0.5	356	32	298	0.89
113 44 0200	14 x 18	40-200	0.5	472	41	422	1.18
113 44 0340	14 x 18	60-340	1	572	41	545	1.55



Data Analyzers

Test Benches

Transducers

Accessories

Software

Services