Screwdriver Bit Quotation Worksheet



For quotation only. Not an order.

NAME			TITEL				
COMPANY							
ADRESS			CITY		STATEZIP		o
E-MAIL			PHONE		FAX		
Style	Point-Size	Style	Point-Size	Style	Point-Size	Style	Point-Size
□ Phillips		□ Torx® □ □ Frearson/		☐ Frearson/Re	ed Prince	☐ Torx-Set®	(+) —
☐ Phillips ACR®	Phillips ACR® 🛨		lus® 🌑 🗆 Socket Head		d •	☐ Triple Square	
☐ Sloted	⊖	☐ Pozidriv	® *	□ Square		☐ Tri-Wing	<u> </u>
Drive Type Size Nylon Covers Requirements							
☐ Hex Insert	ex Insert		Components To Be Covered		Cover Features		
☐ Hex Power			☐ Bit only		\square Flush with tip of bit		
TIEV LOME!			☐ Bit and Bit Holder		☐ Exposed tip of bit		
☐ Threaded — ☐ Threaded					☐ Retractable		
☐ Female Square					☐ Embedded magnets		
				☐ Press fit			
☐ Other ————					 Free-spinning (able to spin independently of part being covered) 		
5.					☐ O.D. limitations (must specify)		
Dimensions A					$\ \square$ Other considerations (must specify)		
		B					
A. Overall Length	— С ———	-					
B. Body Diameter			Bit holder drives for insert bits				
C. Turned Length			☐ Magnetic☐ O-Ring Retention		Bit Holder Drive Types Size		
			☐ Standard (Retaining Groove)		☐ Hex Drive		
			☐ Quick Release		☐ Female Square ———		
			☐ Other		Other		
Quantity			Additional _				
Applied or Driving Torque	.						